



7Oaks

TECHNICAL INFORMATION

PRODUCT REFERENCE

Codes	701, 702, 703, 706, 708, 710
Species	European Oak
Grade	ABCD
Size (L x W x Thickness/top) mm	1900 x 190 x 14/3mm
Board Type	Tongue & Groove
Pattern	1 Strip
Structure	Mixed Eucalyptus & poplar
Edging	Mixed-bevel
Pack Size	2.166m ²
Pack Weight	20kg
Pack Length	1920mm
Pieces Per Pack	6
Nesting	25%
Top Layer	3mm European Oak
Surface Finish	Brushed UV Oiled / UV Lacquered (A/ Oxide finishing if UV Lacquered) with Gloss 5-10%
Environmental Rating/Biological Durability	Class 1
Maintenance	Refer to website: www.7oakstimber.com.au/care-instructions www.artisancollective.co.nz/timber-flooring/ brand/7oaks

INSTALLATION METHODS

Fully bonded	Yes*
Floated on underlay	Yes*
Over under slab heating	Yes*

*Subject to compatible subfloor and correct installation (Refer to installation instructions)



TEST INFORMATION & OTHERS

Origin	France
EUTR	Legally harvested timber
FSC	N/A
Janka hardness rating	1360 LBF (7.0)
Slip testing	AS 4586-2013- P2
Australian reaction to fire- FLOOR	AS ISO 9239.1-2003
Australian reaction to fire- WALL	AS ISO 9239.1-2003
Release of formaldehyde	E1
Release of 4-phenylcyclohexene	≤5 PPM
Warranty- Domestic	20 year wear & lifetime structural
Warranty- Commercial	10 year wear & lifetime structural

INSTALLATION & WARRANTY

All 7Oaks floors must be installed by a competent approved installer who will have the necessary skills and take individual site circumstance into account. 7Oaks warranty will only apply to floors which have been installed according to the 7Oaks installation instructions.

Please note this technical sheet was written by 7Oaks PTY LTD . All information has been specified correctly while writing and publication of the sheet. The company reserves the right to change the specification of this product at any time without prior notice to third parties.

For more information please contact Artisan Collective.

PHONE: (09) 302 2499

EMAIL: sales@artisancollective.co.nz





7Oaks